



Installation Instructions for Décor Stacked Stone

Source – China

Colours:

- | | |
|-----------------------------|----------------------------|
| 1. Ivory - Off White | 2. Shimmer - Mushroom/Pink |
| 3. Bisque - Deep red/orange | 4. Russet - Deep red/brown |
| 5. Onyx - Black | 6. Alpine - Green |

Size: 600mm x 150mm

Thickness: 20 – 40mm

Appearance: Natural Slate stacked with shade and surface differences.

Production: Small pieces of stone epoxy glued together to make a panel.

Décor Stacked Stone enables a surface to be clad with stone to provide a decorative stone appearance. The panels are split on the face side and sawn on the back to provide a natural stone wall with a minimum of cost and effort.

Technical Instructions for installing Décor Stack Stone.

1. Surface must be solid and suitable to hold weight with a clean surface.
2. Application of a waterproofing should be applied if required.
3. Prepare the adhesive mix according to the manufacturers' specifications. *Products that we recommend that you use include Mapei Kerabond plus, which is a cement based powder adhesive mixed with Isolastic which is a latex, designed to improve the performance and durability of Kerabond Isolastic which allows you to bond heavy tiles and natural stone.
4. When using panels in water features ensure the adhesive is suitable for water immersion.* Mapei produce a product that is designed to be used in under water applications.
5. Apply adhesive to wall area to be covered using a minimum 8mm notched trowel. Ensure adhesive covers the whole wall where panels are to be placed. Do not work more than 15 minutes in front.
6. Firmly press panels into position. A brick bond or random pattern can be adopted.
7. Mitre cut corner pieces if required.
8. Sponge off adhesive residue immediately.
9. Apply one coat of Dura-Slate Sealer for a deeper colour finish or one coat of Dura Slate Finish-Primer for a natural finish, if required.

Note: James Hardie, the makers of “Blue Board” DO NOT recommend the use of Harditex Blue Board for use with stack stone. The approximate weight of 40kg per m² precludes the use of this product as it is not capable of supporting this weight, especially where moisture is involved.

Applications: Suitable for commercial and residential exterior and interior wall, column and feature cladding including foyers, courtyards living areas, restaurants and pool features.

Décor Pebble (Aust) P/L

Tel: (03) 9888 9888
Fax: (03) 9888 9884

84-90 Highbury Rd
Burwood Vic 3125
Postal Address: P.O. Box 442 Vermont Vic 3133

Email: sales@decorpebble.com.au
Web: www.decorpebble.com.au